


## IRIS TTE loop

### Loop Expander, TTE Communication Protocol


#### Description

IRIS TTE loop is a loop expander for 1 loop in IRIS Addressable Fire Alarm Systems. The loop expander supports TTE communication protocol and is designed to operate with SensolIRIS detectors, modules and sirens.



#### Technical and Environmental Specifications

Communication Protocol	TTE (Teletek Electronics)
Maximum Current Consumption	500mA
Maximum number of devices	up to 250
Wire Gauge for terminals	0.4mm <sup>2</sup> - 2.0mm <sup>2</sup>
Operating temperature	-10°C to +65°C
Relative humidity resistance	(93 ± 3)% @ 40°C
Weight (including base)	~30g
Dimensions	75x80mm



#### Packing Information

- **Single packing box** - 1 unit IRIS TTE loop, dimensions 108 x 108 x 46 mm

#### Compatible Product Range

- **IRIS** - Addressable Fire Panel
- **SensolIRIS detectors** - T110, T110 IS, S130, S130 IS, M140, M140 IS
- **SensolIRIS call points** - MCP150
- **SensolIRIS modules** - MIO, MC-Z, MOUT, MISO, MINP, GAS
- **SensolIRIS sirens** - WSOU, WSST, BSOU, BSST

#### Contact Information: